



Feeding technology systems

- CAD/CAM feeding systems
 Clean room feeding systems
 Flexible feeding systems
 Disentangling systems



Feeding technology components & systems




Feeding technology

Movement/Drives/ Buffering

Afag vibratory feeders with reactive force compensation compensate vibration forces in the drive unit and therefore prevent vibrations being transferred to the environments, as well as reciprocal interference on multiple drives (cross-talk).

They stand for the highest precision interfaces with minimum gaps, as rubber buffers are not required for the linear feeders in particular. This guarantees reliable operation and highest availability of the entire feeding system.







- Large installation surface for the conveyor track
- Long and heavy conveyor tracks can be inserted (up to 600 mm in length)
-) 115 V/60 Hz or 230 V/50 Hz
- Max. speed 7 m/min



Bowl feeder drives BF/WV

-) 115 V/60 Hz or 230 V/50 Hz
- > Permissible bowl weights from 0.16 kg to 30 kg
- Clockwise or counterclockwise rotational direction
- Throwing angle in 12° and 18° for BF- and 20° and 25° for WV drives



Feeding bowls BB/BB FDA

- Perfect adjustment to tool sizes and tolerances
- Complete reproducibility
- Available in FDA version
- Optionally available with 3 designs of standard helix (radial, grooved or step helix)



Refilling units NVB/NVD/NBB


- Vibration and belt-driven hopper
- > Fill quantities from 0.5 litres to 40 litres
- > Fill weights from 1.7 kg to 40 kg
- Hopper interior with variable incline (NVB)



Flexible feeding component aflex qc

- Time-optimized bulk material separation
- Especially for part sizes/product variants that change frequently
- Standardized interfaces for robot and axis systems

Control concepts







Control concept

- Autonomous operation of feeding systems via the Smart Box
- IRG1-S for 115 V/60 HZ or 230 V/50 Hz vibration conveyors
- IRG1-MS Motor control unit, 230/115 VAC, 2A


Frequency control units PSG1/SIGA

- PSG1 for piezo linear feeders in the HLF-P range
- SIGA for vibration feeders (magnetic drive)

Standards

Chrome-Line components

The standardized Chrome-Line components reduce costs and delivery times thanks to optimized quality in conjunction with a modular design for the feeding stations. Well-known station layouts, and therefore standard stations that can already be integrated in the planning phase, as well as uniform, corrosion-protected surfaces complete the Afag building block principle with regard to the feeding technology components.



Customer-specific drives

- Application-based development co-operation including designing, prototype construction and series production
- Customer-specific linear and spiral conveyors with 24 V/115 V/230 V AC operating voltage
- For special applications in diverse sectors such as
 Providing connection elements in riveting and welding technology
 - Crimp processes in cable processing
 - Counting, weighing, dosing in packaging technology



Services

- Providing drive technology basic training and workshops about drives and applications
- Maintenance, spare and wear parts service
- Diagnostics with innovative QRG1 laboratory measurement device
- Controlled series production with quality assurance thanks to drive check and documenting relevant, drive-specific parameters







CAD/CAM feeding systems

- 100% engineered
- Maximum system availability
- Complete reproducibility
- Cost benefits for repeat orders
- High precision manufacturing thanks to 5-axis simultaneous processing and using CAM
- Primary polymer feeder bowl material proven 10,000 times



Clean room feeding systems

- Verified clean room suitability according to ISO class 7
- Construction standards for medical applications guarantee easy cleaning
- Multiple part provision, preferably with electrical Afag handling
- Feeder bowls made of FDA polyamide, aluminium or stainless steel materials
- Use of medically-suitable materials with material certificate
- Sorting bowls made of high-alloy, polished stainless steel sheets








Flexible feeding systems

- Wide range of variants
- Short changeover times
- Active 3-dimensional conveyance material manipulation
- Combination of in-house Aflex components and electrical handling systems
- Standardized vision and control concept
- Unlimited reuse of system components



Disentangling systems

- The range of disentangling systems available enables ideal adjustment to the individual application
- Reliable disentangling and separation of springs and other conveyed materials
- Innovative approaches for difficult part sizes
- High reliability thanks to automated suppression
- Autonomously usable electrical spring separation with linear motor technology
- Decentralized integrated control system (drum feeder)







Feeding. Handling. Transport.

We are Afag

As a leading provider, Afag has been developing and producing components for assembly automation in the areas of feeding, handling and transport for more than 65 years.

Afag has made it its target to use state-ofthe-art technologies and innovative solutions to meet the high demands of the global automation industry. Thousands of handling modules as well as feeding and transport systems sold by Afag represent the very good quality and reliability of our products.

We have more than 300 employees in our subsidiaries in Switzerland, Germany, China and the USA. There, we produce solutions that are used in all producing industries: From automotive to consumer goods, food, machines, medicine, pharmaceuticals and cosmetics to the watchmaking industry.

Thanks to our sales partners in more than 30 countries, our customers around the world can enjoy professional consulting, planning and service.

By choosing the Afag Group, you have selected a reliable, internationally operating provider of feeding, handling and transporting equipment. But Afag is no longer just a pure provider of automation technology components. Through its professional engineering, installation and commissioning services, we now also offer you solutions for your subtasks.

As an innovative partner, we want to design the future with you. For example, you can talk to us about our IOL-capable components, flexible feeding or robotics.

Our service

- Product training at the customer's facilities or at Afag
- Repair service
- Phone support
-) Consultation and optimisation of applications on site
- Remote maintenance via TeamViewer
- Calculations and design of applications
- Implementation of OEM solutions



LTM & LTS



Linear transport module (vertical) (LTM-V)

Flexible infeed lengths, high payloads, two standard workpiece carrier widths. Optional motor interface with third-party motors.





Linear transport module (horizontal) (LTM-H)

The alternative to the rotary indexing table. The horizontal structure facilitates the circumferential allocation of all workpiece carriers. The varied installation possibilities allow different workpiece machining. Increased repeat accuracy.





Linear transfer system (LTS)

Standard modular kit with high-quality components.



Feeding Technology

Components

aflex qc Diverse application possibilities




aflex 400 lv

Reactive force compensation, tool-free quick-change system and numerous integration options



Flip conveyor



Linear feeder

Compact design with optimised reactive force compensation



Bowl feeder drives





Refill hoppers

Vibration and belt hoppers



Feeding bowls

Wear-free polymer in black and FDA version



Control devices

Modular combination design with Afag control units



Solutions

feeding technology solution

100% reproducible manufacturing



feeding technology solution for clean rooms Particle emissions

Particle emissions checked



Flexible feeding technology solution

Top variant flexibility with the aflex vibration platform



Multi track feeder

Multi-lane feeding with hopper system

NEW CONCEPT STUDY

Smart FEG Air turbulence in the parts container



Drum conveyor

Stand-alone disentangling system with decentralized, integrated control system and intelligent separation



Handling

Gripping

GM Drive/pliers combinable



SG Programmable stroke range



UG Parts detection sensor



PG 16 NN/NO/NC High-precision chuck guidance, miniature design, gripping force securing



GE Compact, fast and a high output density



NEW





NEW

Handling

Turning



RA Endless rotation without moving cables



DG Shortest rotating gripper within its performance class



SREH-50-IOL

Smart rotary module, integrated controller, highly flexible implementation, embedded technology

CR Compact style

RE

High



RM Optional intermediate positions



GMQ/RE

Endless turnable Pneumatic grippers



GM/RM Modular combination



Linear



PDZ

Toothed belt axis, max. length 5260 mm

OZ



SA



Handling


Systems



LM



PDL





CS



ES

Freely programmable



LE





EPS midi XYZC Dynamic even at

higher loads



H-Portal with two slides

Dynamic for large areas and higher loads

() afag

Afag Automation AG

Luzernstrasse 32 6144 Zell

Afag GmbH

Wernher-von-Braun-Straße 1 92224 Amberg Germany

Afag Engineering GmbH

Gewerbestraße 11 78739 Hardt Germany

Afag Automation North America

Schaeff Machinery & Services LLC.

820 Fessler's Parkway, Suite 210 Nashville, TN 37210 USA

Afag Automation APAC

Afag Automation Technology (Shanghai) Co.,

Ltd. Room 102, 1/F, Bldg. 56, City Of Elite No.1000, Jinhai Road, Pudong New District Shanghai, 201206 China

